

FOCUSLITE®



ISO 9001:2000



Company address: No.91 ,Nantou Ave. Dong, Nantou town,Zhongshan City, China 528427

Company address: Show room address : No. S-11,Y23 building ,England cluster,International city,50819 Dubai
UAE

FOCUSLITE®



ISO 9001:2000



Company address: No.91 ,Nantou Ave. Dong, Nantou town,Zhongshan City, China 528427

Company address: Show room address : No. S-11,Y23 building ,England cluster,International city,50819 Dubai
UAE

FOCUSLITE®



ISO 9001:2000



Company address: No.91 ,Nantou Ave. Dong, Nantou town,Zhongshan City, China 528427

Company address: Show room address : No. S-11,Y23 building ,England cluster,International city,50819 Dubai
UAE

FOCUSLITE®



ISO 9001:2000



Company address: No.91 ,Nantou Ave. Dong, Nantou town,Zhongshan City, China 528427

Company address: Show room address : No. S-11,Y23 building ,England cluster,International city,50819 Dubai
UAE

FOCUSLITE®



ISO 9001:2000



Company address: No.91 ,Nantou Ave. Dong, Nantou town,Zhongshan City, China 528427

Company address: Show room address : No. S-11,Y23 building ,England cluster,International city,50819 Dubai
UAE

FOCUSLITE®

Die-cast Aluminum
Excellent Heat Dissipation



ISO 9001:2000



Company address: No.91 ,Nantou Ave. Dong, Nantou town,Zhongshan City, China 528427

Company address: Show room address : No. S-11,Y23 building ,England cluster,International city,50819 Dubai
UAE

FOCUSLITE[®]

IP65 waterproof rating

Effectively waterproof fog,
dust, resist the kitchen, bathroom wet environment



ISO 9001:2000



Company address: No.91 ,Nantou Ave. Dong, Nantou town,Zhongshan City, China 528427

Company address: Show room address : No. S-11,Y23 building ,England cluster,International city,50819 Dubai
UAE



FCS-Deep anti-glare roundsquare surface mounted downlights

Description:

Deep anti-glare recessed downlight

UGR anti-glare value < 19

Surface treatment: sand white

Anti-glare cover color: black, white

Material/process: aluminum/integrated die-casting

Voltage: ADC12

Beam angle of reflector cup: 45°

Compatible light source brackets: Cree 1304, 1816, 1830, 1507, Citizen 020, 2520, Citizen 030

SPECIFICATIONS

| Lamp model | 2501P | 3001P | 4001P | 5001P | 6001P | 8001P |
|---------------------------|-------|-------|---------|------------|------------|------------|
| Diamete | 85MM | 105MM | 131MM | 150MM | 191MM | 215MM |
| opening | 75MM | 95MM | 115MM | 135MM | 175MM | 200MM |
| Height | 54MM | 65MM | 75MM | 80MM | 95MM | 105MM |
| Power | 12W | 18W | 25-30W | 30-38W | 40-50W | 50-60W |
| Lumino us surface | 11mm | 11mm | 11/14mm | 16/17/21mm | 16/17/21mm | 16/17/21mm |
| Beam angle of light | 45° | | | | | |



Company address: No.91 ,Nantou Ave. Dong, Nantou town,Zhongshan City, China 528427

Company address: Show room address : No. S-11,Y23 building ,England cluster,International city,50819 Dubai
UAE