







ISO 9001:2000













loh

ISO 9001:2000





FVCUSLITE®



Strictly selected

Aluminum material is good for heat dissipation, durable and long lifespan.

♦COB LED Light source

High color rendering, uniform luminescence, no light spoteye protection



◆Aluminum radiator

Thickened aluminum heat sink with air convection design for efficient heat dissipation from heat turbines.













FVCUSLITE®



Installation Methods

| 1 | | Ceiling | 2 | Mountinghole | Ceiling |
|---|------------------|----------------|----------------|--------------|----------|
| | Cutting mounting | hole | <u></u> | DDMD, | ownlight |
| | | | | | |
| | RoHS | (iso 9001:2000 | CE CUUS LISTED | F© (((-)) | |

FVCUSLITE®

Easy Installation

Meet your lighting needs













New H series waterproof downlight

Description:

Deep anti-glare embedded downlight UGR anti-glare value < 19 Surface treatment: sand white, anti-glare cover Color: black, bright silver, material/process: aluminum/ADC12/integrated die-casting beam of light Angle: 15 $^{\circ}$ /24 $^{\circ}$ /36 $^{\circ}$ /55 $^{\circ}$ Adapted light source bracket: Cree 1304/1507 Citizen 020

SPECIFICATIONS

| Lamp model | 2501H | 3001H | 4001H | 5001H | 6001H | 8001H | | |
|------------------------------|-----------------|-------------------|-------------------|-------------------|-------------------|-------------------|--|--|
| with or without border | No | No | No | No | No | No | | |
| Diamete r | 85MM | 105MM | 131MM | 150MM | 191MM | 215MM | | |
| Openin g | 75MM | 95MM | 115MM | 135MM | 175MM | 200MM | | |
| Height | 54MM | 65MM | 75MM | 80MM | 95MM | 105MM | | |
| Power | 12W | 18W | 20-30W | 30-38W | 40-50W | 50-60W | | |
| Lumino us surface | 11mm | 11/14/16/17 mm | 11/14/16/17 mm | 11/14/16/17 mm | 11/14/16/17 mm | 11/14/16/17 mm | | |
| Beam angle of light | 15°/24°/36°/55° | | | | | | | |

